



## PRODUITS-IDC TA-330X-X EXTREME WEATHER FOIL

All-weather duct tape, working temperature range of -35°F to 260°F (-37°C to 126°C), plain dead soft aluminum foil-faced duct systems.

### Applications

Designed for taping joints and seams in duct work for heating, air conditioning and refrigeration systems. Specifically intended for use over a wide range of application temperatures. Suitable for general repairs and a variety of insulation uses.

### Features & Benefits

Special adhesive system with aggressive adhesion even at -35°F. Plain dead soft aluminum foil backing. Foil backing is extremely conformable. High adhesion and Quick Stick. Matches most laminated duct work.

### Product Construction

Adhesive: Acrylic  
Backing: Foil

### Special Conditions

Cold Temperature  
Low VOC

### Certifications

LEED - Contributes toward satisfying EA Credit 1 (Optimize Energy Performance)

LEED - Contributes toward satisfying EQ Credit 4.1 (Low Emitting Materials)

### Performance Specifications

| Measurement                     | US Value     | Metric Value | Test Method |
|---------------------------------|--------------|--------------|-------------|
| Adhesion to Backing             | 40oz/in      | 44.8g/mm     | PSTC-1      |
| Adhesion to Steel               | 55oz/in      | 61.6g/mm     | PSTC-1      |
| Minimum Application Temperature | -25°F        | -32°C        |             |
| Temperature Range               | -35 to 260°F |              |             |
| Tensile                         | 14lb/in      | .25kg/mm     | ASTM D-1000 |
| Thickness                       | 3.5Mils      | .889mm       | ASTM D-1000 |